



Jenco Canada Inc.

72 Devon Rd, Unit # 7,8,9,10, Brampton, Ontario, L6T 5B4
Off-905-794-1433 | Mobile-416-892-3959

LED Flood Light 100W ST-LFL100N



Applications

- Public landmark, historic sites, commercial building, sculpture, bridge, mining workshop, billboard, tunnel, ancient tree, night scape, decorative lighting etc.

Features


- Free Adapter Available
- Housing: White/Grey/Black color Available
- Lifespan: 50,000 hours
- **Warranty: 5Years**
- CREE XML CHIPS
- Driver: MOONS
- Low temperature rise 40deg c = increased longevity of the complete fitting.
- **UL, DLC LISTED UL NO.: E361637**

Specifications

- Input voltage: 95-305VAC
- Beam Angle: 120°
- Light efficiency: 95%
- Lumens: 10000lm
- Available Color Temperatures: 2700-9000K
- LED: CREE XML
- Driver: MOONS
- Enclosure Rating: IP65
- Power factor: >0.95
- CRI: >=75Ra
- Package information: Size 42*17*52cm Weight:7.65kg 1PCS/Carton box

Installation Instructio :

1. Cut two hole that the distance and the size like "A" in the framework. Lock the floodlight with bolt and nut;



2. Rotating the light body to adjust the required cast light angle, install the hex-head screws tight;

