

DC LED Ceiling & Wall light

Job Information		
Project Name		Type
Location		
Quantity		Date
Contact/Phone		
Notes		

Features

Product Specification:

- A. Multi-faceted fixture interior engineered to maximize LED module performance.
- B. LED module designed to deliver maximum light levels to work surface without fixture glare.
- C. Opaque white acrylic lens finish provides maximum optical comfort and effective light distribution.
- D. Highly efficient 3000K leds provide Warm White light (80+ cRI).

Constructions:

- A. Formed fixture pan with access holes to junction box.
- B. Aluminum LED module tray directs heat away from electronic components
- C. Tool-less access to fixture components with removal of 3 decorative nuts

LED Advantages:

- A. Energy saving of more than 50% over traditional CFL technology.
- B. Reduced maintenance costs with LED components rated over 50,000 hours
- C. Full 5-year warranty available on all components.

Operating Temperature

-20° C ~ 40° C (-4° F ~ 104° F)

Environment

- For indoor use only.
- Suitable for wet locations.

Options

- A. (12", 14", 16", 18", 22")housing
 - B. Various lumen packages to suit every application
- Easy to install



CONTEMPORARY ROUND GLASS WITH CONCENTRIC RINGS

Ceiling Mount

Line Voltage LED



Dimming : 10-100% Triac, ELV, MLV, CFL/LED

LED Life : 50,000 hours

Model	Size	Watt	Lm*	Lm/W
CSC3001-LED	9-7/8" Ø *3 1/2"H"	16W	1050	65.6
CSC3002-LED	12" Ø *3 5/8"H"	18W	1260	70
CSC3003-LED	14" Ø *3 1/4"H"	22W	1470	66.8
CSC3004-LED	16-1/4" Ø *4 3/4"H"	28W	1890	67.5
CSC3005-LED	18" Ø *4 3/4"H"	31W	2100	67.7
CSC3006-LED	23-5/8" Ø * 5"H"	34W	2310	67.9



Notes: Accessories are sold separately. For additional options please consult your representative. Due to our continued efforts to improve our products, product specifications are subject to change without notice.

Ordering Guide

SIZE	- CCT	- FINISH
<input type="text"/>	<input type="text"/>	<input type="text"/>
12" Ø	30 - 3000K	BN - Brushed Nickel
14" Ø	40 - 4000K	WH - White
16" Ø		
18" Ø	27 - 2700K**	
22" Ø		

* Based on 3000K

** Contact Factory for 2700K availability